

GLOBAL TECH LAUNDRY

Innovative, quality laundry solutions

Global Tech Laundry
www.globaltechlaundry.com

JOS-HS

Washer Extractor - High Spin

洗衣機提取器 - 高旋轉



High extraction speed, and the speed can be adjusted according to customers needs to improve the washing effect. 提取速度快，且可根據客戶需要調整速度，提高洗滌效果。

Imported parts all the parts are imported brands, to ensure the performance of the machine, prolong the service life. 進口零件 所有零件均採用進口品牌，保證機器的性能，延長使用壽命。

Delicate care about clothes It is more suitable for cleaning heavy fabrics such as quilts, pillows and so on. 精緻呵護衣物 更適合清洗被子、枕頭等厚重的織物。

7" Touch color screen Large screen, operation visualization, 50 sets customize control program, 8 detergent pump for feeding, 3 water inlets: cold water inlet, hot water inlet and soft water inlet. 7英寸觸摸彩屏大螢幕，操作可視化，50組定製控制程式，8個洗滌劑泵供料，3個進水口：冷水進水口、熱水進水口和軟水進水口。

Durable & Stable structure Heavy duty aluminum support ring enables the machine run smoothly and stably under 800rpm high speed. Three bearings and oil seals extend the life. 耐用且穩定的結構 重型鋁製支撐環使機器在800rpm的高速下平穩運行。三個軸承和油封延長了使用壽命。

8 SOAP INJECTION for compatibility with any external automatic chemical dosing system FULL 8 肥皂注射，與任何外部自動化學加藥系統完全兼容

SUSPENSION composite shock absorption technology with German brand shock absorbing components achieve ultra-low vibration and eliminate the need for foundations. 懸架複合減震技術搭配德國品牌減震元件，實現超低振動，無需地基。

STRONG, PRODUCTIVE, TECHNOLOGICAL AND SIMPLE 強大、高效、技術、簡單

GLOBAL TECH LAUNDRY

Innovative, quality laundry solutions

Global Tech Laundry
www.globaltechlaundry.com

TECHNICAL DATA 技術數據

| MODEL - 型號 | JOS-40-HS | JOS-60-HS | JOS-80-HS | JOS-100-HS | JOS-120-HS |
|------------------------|-------------|----------------|----------------|---------------|---------------|
| Capacity 能力 | 40 kg | 60 kg | 80 kg | 100 kg | 120 kg |
| Cylinder Diameter 氣缸直徑 | 900 mm | 1078 mm | 1078 mm | 1310 mm | 1310 mm |
| Cylinder depth 圓柱體深度 | 626 mm | 620 mm | 820 mm | 746 mm | 816 mm |
| Cylinder volume 氣缸容積 | 400 Dm3 | 566 Dm3 | 750 Dm3 | 1000 Dm3 | 1100 Dm3 |
| Single motor 單電機 | 5 cv (4 kw) | 10 cv (7,5 kw) | 10 cv (7,5 kw) | 15 cv (11 kw) | 15 cv (11 kw) |
| Wash Speed 洗滌速度 | 30-40 rpm | 30-40 rpm | 30-40 rpm | 30-38 rpm | 30-38 rpm |
| Extract Speed 提取速度 | 760 rpm | 700 rpm | 700 rpm | 650 rpm | 650 rpm |
| G Factor G 因數 | 300 | 300 | 300 | 300 | 300 |
| Water inlet valve 進水閥 | 1.1/4" | 1.1/4" | 1.1/4" | 2" | 2" |
| Drain valve 排水閥 | 3" | 5" | 5" | 2 x 5" | 2 x 5" |
| Overall Width 總寬度 | 1230 mm | 1619 mm | 1619 mm | 1774 mm | 1774 mm |
| Overall Depth 總深度 | 1433 mm | 1492 mm | 1692 mm | 1761 mm | 1828 mm |
| Overall Height 總高度 | 1735 mm | 1965 mm | 1965 mm | 2092 mm | 2092 mm |
| Net Weight 淨重 | 1190 kg | 1910 kg | 2200 kg | 3170 kg | 3220 kg |



Global Tech Laundry
www.globaltechlaundry.com

Tel. + 86 18818871709 / +86 13928709709
N° 36F, 2F, Block B, Xinsanding Business Center, Yansha East Road
Nanpu, Panyu District, Guangzhou, P.R. China – Zip Code 511431